

1600 Series



مفتوح	رقم المنتج		ثقب قطر (د ملم)	خارجي قطر (دي ملم)	عرض B مم	عرض B1 مم	نصف القطر (آر إس دقيقة) مم	(درجة التحميل نيوتن) ثابتة كور	
	درع	مختوم						ديناميكي كرس	ثابتة كور
1640	1640ZZ	1640 2RS	22.23	50.80	14.29	14.29	0.60	10.70	5.81
1641	1641ZZ	1641 2RS	25.40	50.80	12.70	12.70	0.60	10.70	5.81
1638	1638ZZ	1638 2RS	19.05	50.80	14.29	14.29	0.60	10.70	5.81
1633	1633ZZ	1633 2RS	15.88	44.45	12.70	12.70	0.60	12.92	6.22
1635	1635ZZ	1635 2RS	19.05	44.45	12.70	12.70	0.60	12.92	6.22
1630	1630ZZ	1630 2RS	19.05	41.28	12.70	12.70	0.60	9.39	5.08
1623	1623ZZ	1623 2RS	15.88	34.93	11.11	11.11	0.60	7.77	3.61
1628	1928ZZ	1628 2RS	15.88	41.28	12.70	12.70	0.60	9.58	4.81
1622	1622ZZ	1622 2RS	14.29	34.93	11.11	11.11	0.60	7.77	3.61
1620	1620ZZ	1620 2RS	11.11	34.93	11.11	11.11	0.60	7.77	3.61
1621	1621ZZ	1621 2RS	12.70	34.93	11.11	11.11	0.60	7.77	3.61
1616	1616ZZ	1616 2RS	12.70	28.58	9.53	9.53	0.30	5.12	2.40
1614	1614ZZ	1614 2RS	9.53	28.58	9.53	9.53	0.30	5.12	2.40
1615	1615ZZ	1615 2RS	11.11	28.58	9.53	9.53	0.30	5.12	2.40
1607	1607ZZ	1607 2RS	11.11	23.02	7.94	7.94	0.30	2.70	1.27
1605	1605ZZ	1605 2RS	7.94	23.02	7.94	7.94	0.30	3.31	1.38
1606	1606ZZ	1606 2RS	9.53	23.02	7.94	7.94	0.30	3.33	1.41
		1604 2RS	9.53	22.23		8.73	0.30	3.33	1.41
1604	1604ZZ		9.53	22.23	7.14	7.14	0.30	3.33	1.41
1603	1603ZZ		7.94	22.23	7.14	7.14	0.30	3.31	1.38
		1603 2RS	7.94	22.23	7.14	8.73	0.30	3.31	1.38

1600 Series

		1602 2RS	6.35	17.46		7.94	0.30	2.26	0.84
		1601 2RS	4.76	17.46		7.94	0.30	1.98	0.74
1602	1602ZZ		6.35	17.46	6.35	6.35	0.30	2.26	0.84
1601	1601ZZ		4.76	17.46	6.35	6.35	0.30	1.98	0.74